



### TECHNICAL CHARACTERISTICS

- > Seat depth: 398 mm
- > Overall height: 911 mm
- > Seat height: 540 mm
- > 30 x 50 mm tubular steel frame, thickness: 2 mm
- > With armrests, thickness: 8 mm
- > Base plates: 100 x 40 mm, thickness 5 mm
- > Footrest 50 x 30 mm

#### Steel and wood version:

- Three lengths: 600, 1200 or 1800 mm (for the 1800 mm versions, the seat is reinforced with a galvanised steel cradle)
- Seat in PEFC certified oak, thickness: 36 mm, slat width: 115 mm

#### All-steel version:

- Length: 1800 mm
- Seat and backrest in folded galvanised steel sheet, thickness: 2 mm, slat width: 120 mm

### INSTALLATION

- > On base plates
- > Flat packed for self assembly (all wooden slats are pre-drilled for easy assembly)

### OPTION

- > Central armrest for bench: width 60 mm, thickness 8 mm  
*(recommendation: one armrest for a 1200 mm seat and two armrests for a 1800 mm seat)*

### PRODUCT CODES

	Steel and wood version	All steel version
Length 600 mm	209620	-
Length 1200 mm	209621	-
Length 1800 mm	209622	209626
<b>Optional</b> central armrest	209629	

### FINISH PAINTED

- > Structure: steel, zinc-primed and painted in our colours
- > Steel and wood version: seat and back in raw wood finish, light oak or mahogany
- > All steel version: seat and back galvanised and painted in monochrome or twin colours



Code 209620



Code 209621



Code 209626



### DRAWING

